

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations
Date of Issue: 03/20/2020

Version: C

SECTION 1: IDENTIFICATION

1.1. Product Identifier
Product Form: Mixture
Product Name: Alcohol Wipes
Product Code: CSWA001

1.2. Intended Use of the Product

Use of the Substance/Mixture: Low level disinfection surface wipes.1.3. Name, Address, and Telephone of the Responsible Party

Company

Case Medical Inc. 50 West St. Bloomfield, NJ 07003

201-313-1999

www.casemed.com info@casemed.com

1.4. Emergency Telephone Number

Emergency Number : For Hazardous Materials [or Dangerous Goods] Incidents ONLY

(spill, leak, fire, exposure or accident), call CHEMTREC at CHEMTREC®, USA & CANADA: 001 (800) 424-9300

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US Classification

Flam. Liq. 2 H225
Eye Irrit. 2A H319
Muta. 1B H340
Carc. 1B H350
STOT SE 3 H336

Full text of hazard classes and H-statements : see section 16

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



GH507



Signal Word (GHS-US) : Danger

Hazard Statements (GHS-US) : H225 - Highly flammable liquid and vapor.

H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness. H340 - May cause genetic defects.

11540 - May Cause genetic de

H350 - May cause cancer.

Precautionary Statements (GHS-US) : P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from extremely high or low temperatures, ignition sources, and

incompatible materials. - No smoking. P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment.

P241 - Use explosion-proof electrical, ventilating, and lighting equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P261 - Avoid breathing vapors, mist, or spray.

07/24/2017 EN (English US) 1/9

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves, protective clothing, and eye protection.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P312 - Call a poison center or doctor if you feel unwell.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P370+P378 - In case of fire: Use appropriate media (see section 5) to extinguish.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier	%	GHS-US classification
Isopropyl alcohol	(CAS-No.) 67-63-0	10 - 70	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Ethyl alcohol	(CAS-No.) 64-17-5	10 - 70	Flam. Liq. 2, H225 Eye Irrit. 2A, H319
2-Pentanone, 4-methyl-	(CAS-No.) 108-10-1	<1	Flam. Liq. 2, H225 Acute Tox. 3 (Inhalation:vapor), H331 Eye Irrit. 2A, H319 Carc. 2, H351 STOT SE 3, H335 Asp. Tox. 1, H304
Solvent naphtha, petroleum, light aliphatic	(CAS-No.) 64742-89-8	<1	Flam. Liq. 1, H224 Skin Irrit. 2, H315 Muta. 1B, H340 Carc. 1B, H350 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid Measures After Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

First-aid Measures After Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

03/20/2020 EN (English US) 2/9

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid Measures After Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

First-aid Measures After Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

Symptoms/Injuries: Causes serious eye irritation. May cause drowsiness and dizziness. May cause genetic defects. May cause cancer

Symptoms/Injuries After Inhalation: High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation.

Symptoms/Injuries After Eye Contact: Contact causes severe irritation with redness and swelling of the conjunctiva.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: May cause genetic defects. May cause cancer.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂). Water may be ineffective but water should be used to keep fire-exposed container cool.

Unsuitable Extinguishing Media: Do not use a heavy water stream. A heavy water stream may spread burning liquid.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Highly flammable liquid and vapor.

Explosion Hazard: May form flammable or explosive vapor-air mixture.

Reactivity: Reacts violently with strong oxidizers. Increased risk of fire or explosion.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection. **Hazardous Combustion Products:** Carbon oxides (CO, CO₂). Irritating or toxic vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not get in eyes, on skin, or on clothing. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric charges. Do not breathe vapor, mist or spray.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Stop leak if safe to do so.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area. Eliminate ignition sources.

6.2. Environmental Precautions

Do not allow uncontrolled discharge of product into the environment. Collect spillage.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable.

03/20/2020 EN (English US) 3/9

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Take precautionary measures against static discharge. Use only non-sparking tools. Avoid contact with eyes, skin and clothing. Do not breathe dust/fume/gas/mist/vapors/spray. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes, on skin, or on clothing.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. Take action to prevent static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment.

Storage Conditions: Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store in a well-ventilated place. Keep container tightly closed. Keep in fireproof place.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

Specific End Use(s)

Low level disinfection surface wipes.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

Isopropyl alc	ohol (67-63-0)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm	
USA ACGIH	ACGIH STEL (ppm)	400 ppm	
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen	
USA ACGIH	Biological Exposure Indices (BEI)	40 mg/l Parameter: Acetone - Medium: urine - Sampling time: end	
		of shift at end of workweek (background, nonspecific)	
USA NIOSH	NIOSH REL (TWA) (mg/m³)	980 mg/m³	
USA NIOSH	NIOSH REL (TWA) (ppm)	400 ppm	
USA NIOSH	NIOSH REL (STEL) (mg/m³)	1225 mg/m ³	
USA NIOSH	NIOSH REL (STEL) (ppm)	500 ppm	
USA IDLH	US IDLH (ppm)	2000 ppm (10% LEL)	
USA OSHA	OSHA PEL (TWA) (mg/m³)	980 mg/m³	
USA OSHA	OSHA PEL (TWA) (ppm)	400 ppm	
Ethyl alcohol	(64-17-5)		
USA ACGIH	ACGIH STEL (ppm)	1000 ppm	
USA ACGIH	ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans	
USA NIOSH	NIOSH REL (TWA) (mg/m³)	1900 mg/m ³	
USA NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm	
USA IDLH	US IDLH (ppm)	3300 ppm (10% LEL)	
USA OSHA	OSHA PEL (TWA) (mg/m³)	1900 mg/m ³	
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm	
2-Pentanone	2-Pentanone, 4-methyl- (108-10-1)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm	
USA ACGIH	ACGIH STEL (ppm)	75 ppm	
USA ACGIH	ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans	
USA ACGIH	Biological Exposure Indices (BEI)	1 mg/l Parameter: MIBK - Medium: urine - Sampling time: end of	
		shift	
USA NIOSH	NIOSH REL (TWA) (mg/m³)	205 mg/m ³	
USA NIOSH	NIOSH REL (TWA) (ppm)	50 ppm	
USA NIOSH	NIOSH REL (STEL) (mg/m³)	300 mg/m ³	
USA NIOSH	NIOSH REL (STEL) (ppm)	75 ppm	
USA IDLH	US IDLH (ppm)	500 ppm	
USA OSHA	OSHA PEL (TWA) (mg/m³)	410 mg/m ³	
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm	

03/20/2020 EN (English US) 4/9

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Exposure Controls

Appropriate Engineering Controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosionproof equipment.

Personal Protective Equipment

: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.









Materials for Protective Clothing

: Chemically resistant materials and fabrics. Wear fire/flame resistant/retardant clothing.

Hand Protection
Eye and Face Protection
Skin and Rody Protection

: Wear protective gloves.: Chemical safety goggles.

Skin and Body Protection Respiratory Protection

: Wear suitable protective clothing.

Wear suitable protective clothing.
 If exposure limits are exceeded or

: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information

: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State : Liquid
Appearance : Clear

Odor : Odor of rubbing alcohol

Odor Threshold : No data available

pH : 6.5 - 7.5

Evaporation Rate : No data available : No data available **Melting Point Freezing Point** : No data available **Boiling Point** : 176.6 °F (80.33 °C) **Flash Point** : 69.8 °F (21 °C) **Auto-ignition Temperature** : No data available **Decomposition Temperature** : No data available Flammability (solid, gas) : No data available **Vapor Pressure** : No data available Relative Vapor Density at 20°C : No data available **Relative Density** : No data available Solubility : No data available **Partition Coefficient: N-Octanol/Water** : No data available Viscosity : No data available

9.2. Other Information No additional information available

SECTION 10: STABILITY AND REACTIVITY

- **10.1. Reactivity:** Reacts violently with strong oxidizers. Increased risk of fire or explosion.
- 10.2. Chemical Stability: Extremely flammable liquid and vapor. May form flammable or explosive vapor-air mixture.
- **10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- **10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.
- **10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers.
- 10.6. Hazardous Decomposition Products: Not available

03/20/2020 EN (English US) 5/9

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects

Acute Toxicity: Not classified

Isopropyl alcohol (67-63-0)		
LD50 Dermal Rabbit	4059 mg/kg	
LC50 Inhalation Rat	72600 mg/m³ (Exposure time: 4 h)	
LC50 Inhalation Rat	72.5 mg/l/4h	
Ethyl alcohol (64-17-5)		
LD50 Oral Rat	10470 mg/kg	
LD50 Dermal Rat	20 ml/kg	
LC50 Inhalation Rat	124.7 mg/l/4h	
2-Pentanone, 4-methyl- (108-10-1)		
LD50 Oral Rat	2080 mg/kg	
LD50 Dermal Rabbit	3000 mg/kg	
LC50 Inhalation Rat	8.2 mg/l/4h	
LC50 Inhalation Rat	11.6 mg/l/4h	
Solvent naphtha, petroleum, light aliphatic (64742-89-8)		
LD50 Oral Rat	>= 5000 mg/kg	
LD50 Dermal Rabbit	3000 mg/kg	

Skin Corrosion/Irritation: Not classified

pH: 6.5 - 7.5

Serious Eye Damage/Irritation: Causes serious eye irritation.

pH: 6.5 - 7.5

Respiratory or Skin Sensitization: Not classified **Germ Cell Mutagenicity:** May cause genetic defects.

Carcinogenicity: May cause cancer.

Isopropyl alcohol (67-63-0)		
IARC group	3	
Ethyl alcohol (64-17-5)		
IARC group	1	
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.	
2-Pentanone, 4-methyl- (108-10-1)		
IARC group	2B	
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity.	
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.	

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): May cause drowsiness or dizziness.

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation.

Symptoms/Injuries After Eye Contact: Contact causes severe irritation with redness and swelling of the conjunctiva.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: May cause genetic defects. May cause cancer.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General : Not classified.

Isopropyl alcohol (67-63-0)		
LC50 Fish 1	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	
EC50 Daphnia 1	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
EC50 Other Aquatic Organisms 1 1000 mg/l (Exposure time: 96 h - Species: Desmodesmus subspicatus)		
LC50 Fish 2	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	

03/20/2020 EN (English US) 6/9

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EC50 Other Aquatic Organisms 2	1000 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)	
Ethyl alcohol (64-17-5)		
EC50 Daphnia 1	9268 - 14221 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
LC50 Fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
ErC50 (Algae)	1000 mg/l	
2-Pentanone, 4-methyl- (108-10-1)		
LC50 Fish 1	496 - 514 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	
EC50 Daphnia 1	170 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
ErC50 (Algae)	400 mg/l (Exposure time 96 h - Species: Pseudokirchneriella subcapitata)	
Solvent naphtha, petroleum, light aliphatic (64742-89-8)		
LC50 Fish 1	>= 8.2 mg/l Exposure time 96 hour Species: Pimephales promelas	
NOEC Chronic Fish	14 day exposure Species: Pimephales promelas LC50: 5.2 mg/l	

12.2. Persistence and Degradability

Alcohol Wipes	
Persistence and Degradability	Not established.

12.3. Bioaccumulative Potential

Alcohol Wipes		
Bioaccumulative Potential	Not established.	
Isopropyl alcohol (67-63-0)		
Log Pow	0.05 (at 25 °C)	
Ethyl alcohol (64-17-5)		
Log Pow	-0.32	
2-Pentanone, 4-methyl- (108-10-1)		
Log Pow	1.19	

12.4. Mobility in Soil No additional information available

12.5. Other Adverse Effects

Other Information : None known.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste Treatment Methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, and international regulations.

Ecology - Waste Materials: Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT

Proper Shipping Name : SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Contains Isopropyl alcohol, Ethyl alcohol)

Hazard Class : 4.1
Identification Number : UN3175
Label Codes : 4.1
Packing Group : II
ERG Number : 133



14.2. In Accordance with IMDG

Proper Shipping Name : SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Contains Isopropyl alcohol, Ethyl alcohol)

Hazard Class : 4.1

Division : 4.1

Identification Number : UN3175

Packing Group : II

Label Codes : 4.1

EmS-No. (Fire) : F-A

EmS-No. (Spillage) : S-I



14.3. In Accordance with IATA

Proper Shipping Name : SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Contains Isopropyl alcohol, Ethyl alcohol)

03/20/2020 EN (English US) 7/9

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Packing Group : II
Identification Number : UN3175
Hazard Class : 4.1
Label Codes : 4.1
Division : 4.1
ERG Code (IATA) : 3L



SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

Alcohol Wipes		
SARA Section 311/312 Hazard Classes	Fire hazard	
	Immediate (acute) health hazard	
	Delayed (chronic) health hazard	
Isopropyl alcohol (67-63-0)		
Listed on the United States TSCA (Toxic Substances Control	ol Act) inventory	
Subject to reporting requirements of United States SARA	Section 313	
SARA Section 313 - Emission Reporting	1 % (only if manufactured by the strong acid process, no supplier	
	notification)	
Ethyl alcohol (64-17-5)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
2-Pentanone, 4-methyl- (108-10-1)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Subject to reporting requirements of United States SARA Section 313		
CERCLA RQ	5000 lb	
SARA Section 313 - Emission Reporting 1 %		
Solvent naphtha, petroleum, light aliphatic (64742-89-8)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		

15.2. US State Regulations

Ethyl alcohol (64-17-5)	
U.S California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of
	California to cause cancer. Ethyl Alcohol is included on the Proposition
	65 list when it is used in alcoholic beverages.
U.S California - Proposition 65 - Developmental	WARNING: This product contains chemicals known to the State of
Toxicity	California to cause birth defects. Ethyl Alcohol is included on the
	Proposition 65 list when it is used in alcoholic beverages.
2-Pentanone, 4-methyl- (108-10-1)	
U.S California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of
	California to cause cancer.
U.S California - Proposition 65 - Developmental	WARNING: This product contains chemicals known to the State of
Toxicity	California to cause birth defects.

Isopropyl alcohol (67-63-0)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Ethyl alcohol (64-17-5)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

2-Pentanone, 4-methyl- (108-10-1)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

03/20/2020 EN (English US) 8/9

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision

Other Information

: 07/24/2017

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR

1910.1200

GHS Full Text Phrases:

Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1B	Carcinogenicity Category 1B
Carc. 2	Carcinogenicity Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 1	Flammable liquids Category 1
Flam. Liq. 2	Flammable liquids Category 2
Muta. 1B	Germ cell mutagenicity Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H224	Extremely flammable liquid and vapor
H225	Highly flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H331	Toxic if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom)

03/20/2020 EN (English US) 9/9